

## F0565 PRODUCT INFO



The COLDTAINER product line includes a large range of state of the art 12V active mobile refrigerated containers. The containers are produced using the rotational molding technology according to the highest standards. They come in a variety of types, internal volumes and internal temperature ranges designed to satisfy all possible demands of professional users in term of temperature controlled transport

- Internal gross capacity 565 litres
- Single piece design is sturdy, durable and lightweight, with no junctions or cold bridges. Made of food grade polyethylene (PE), UV stabilized. Ultra-thick insulation made by PU foam. Designed for an easy cleaning and disinfection
- Direct current cooling units designed for years of use on board of vehicles, providing low energy consumption and resistance to vibrations. Ambient temperature range from -20°C up to +55°C (with reduced specifications)
- Refrigeration system includes 12V compressors, large surface roll-bond evaporators, ventilated high efficiency spiral tube condensers, electronic thermostat with digital display, battery protection system
- NDH version available for the safe transport of sensitive products (i.e. pharmaceuticals, vaccines, blood). It maintains consistent temperature with a smooth air flow distribution, regardless of outside ambient temperature in alignment with GDP
- AC/DC power supplies available as accessories

### Available versions:

- ☐ NDN down to +0°C
- ☐ FDN down to -21°C
- ☐ NDH from +30°C to +0°C



**easy cooling, smart moving**

[www.coldtainer.com](http://www.coldtainer.com)

**F0565**  
**PRODUCT INFO**

Model name	<b>F0565/NDN</b>	<b>F0565/FDN</b>
EE article nr.	816014/00	816014/01
Gross capacity (lt)	565	565
Temperature range (°C)*	down to +0 °C	down to -21 °C
ATP class	FRAX**	FRCX**
Voltage	12-24 Vdc	12 Vdc
Peak Amps (@12Vdc)	18A	25A
Fuse on DC cord	50A	50A
External dimensions (mm)	725 x 1220 x 1650	725 x 1220 x 1650
Weight (kg)	147	155
PU insulation (mm)	100	100
"K" insulation factor	0,31 W/m²K	0,31 W/m²K
Refrigerant gas (type)	R134a	R452A
Refrigerant gas (gr)	n/a	n/a
Cut-out / cut-in voltage	9,6 Vdc-10,9 Vdc	11 Vdc-12,3 Vdc
AC/DC power supply (opt)	560020/00	560021/00

<b>F0565/NDH</b>
816014/02
565
from +30 °C to +0 °C
BRBX**
12 Vdc
18A
50A
725 x 1220 x 1650
160
100
0,31 W/m²K
R134a
133
9,6 Vdc-10,9 Vdc
560020/00

\*with ambient temperature +30°C

\*\*available from Q3/2025

**E57** 10R-060148



032025 rev0 - Copyright©2025 Euroengel srl

