

T0056/T0082 PRODUCT INFO



The COLDTAINER product line includes a large range of state of the art 12V active mobile refrigerated containers. The containers are produced using the rotational molding technology according to the highest standards. They come in a variety of types, internal volumes and internal temperature ranges designed to satisfy all possible demands of professional users in term of temperature controlled transport

- Internal gross capacity 56 litres (T0056), 82 litres (T0082)
- Single piece design is sturdy, durable and lightweight, with no junctions or cold bridges. Made of food grade polyethylene (PE), UV stabilized. Ultra-thick insulation made by PU foam. Designed for an easy cleaning and disinfection
- Direct current cooling units designed for years of use on board of vehicles, providing low energy consumption and resistance to vibrations. Ambient temperature range from -20°C up to +55°C (with reduced specifications)
- Refrigeration system includes 12V compressors, large surface roll-bond evaporators, ventilated high efficiency spiral tube condensers, electronic thermostat with digital display, battery protection system
- FDH version available for the safe transport of sensitive products (i.e. pharmaceuticals, vaccines, blood). It maintains consistent temperature with a smooth air flow distribution, regardless of outside ambient temperature in alignment with GDP
- AC/DC power supplies available as accessories

Available versions:

- ☐ FDN down to -24°C
- ☐ FDH from +40°C to -24°C
- ☐ XF DN down to -35°C



easy cooling, smart moving

www.coldtainer.com

T0056/T0082
PRODUCT INFO

Model name	T0056/FDN	T0056/FDH	T0082/FDN	T0082/FDH	T0082/XFDN
EE article nr.	816003/00	816003/01	816004/00	816004/01	816004/02
Gross capacity (lt)	56	56	82	82	82
Temperature range (°C)*	down to -24°C	from +40°C to -24°C	down to -24°C	from +40°C to -24°C	down to -35°C
ATP class	n/a	n/a	FRCX	BRJX**	n/a
Voltage	12-24 Vdc	12-24 Vdc	12-24 Vdc	12-24 Vdc	12 Vdc
Peak Amps (@12 Vdc)	9A	9A	9A	9A	20A
Fuse on DC cord	25A	25A	25A	25A	30A
External dimensions (mm)	495 x 800 x 500	495 x 800 x 500	560 x 940 x 550	560 x 940 x 550	560 x 940 x 550
Weight (kg)	33	33	35	35	40
PU insulation (mm)	70	70	80	80	80
"K" insulation factor	n/a	n/a	0,36 W/m²K	0,36 W/m²K	0,36 W/m²K
Refrigerant gas (type)	R134a	R134a	R134a	R134a	R404A
Refrigerant gas (gr)	65	65	65	65	100
Cut-out / cut-in voltage	9,6 Vdc-10,9 Vdc	9,6 Vdc-10,9 Vdc	9,6 Vdc-10,9 Vdc	9,6 Vdc-10,9 Vdc	11 Vdc-12,3 Vdc
AC/DC power supply (opt)	560019/00	560019/00	560019/00	560019/00	560020/00

*with ambient temperature +30°C

**available from Q4/2025

E57 10R-060148



032025 rev0 - Copyright©2025 Euroengel srl

